

Platform

0.91 m roll-out deck extension
Fold-down handrails
Self-closing gate
Removable platform console box
Lanyard attach points
Full proportional drive joystick control with integral thumb steer switch
Proportional lift/lower speed control
Joystick enable for lift and drive
Load sensing system
Two speed drive selection

Power & Transmission

Two Wheel Direct Electric Drive
8 x 6V 370 A/hr deep cycle batteries
Automatic traction control
Programmable "Personality" settings
On-board self-diagnostic testing
Detachable battery compartments
23 amp automatic battery charger
Automatic rear wheel brakes
Sculptured ABS hoods

Functional Equipment & Accessories

3 degree tilt alarm and indicator light
Steel scissor guards
240/55 - 17.5 non marking foam filled tyres
Oscillating rear axle
Lifting/tie down lugs
Lubrication free scissor arm bushings
Scissor maintenance prop
AC cable to platform
Ground control selector switch with key lock
Battery condition indicator
Hour meter
Horn
Manual descent pull cable

Available Options

Hydraulic levelling jacks
All motion alarm
Descent alarm
Alarm package ¹
Platform work-lights
Amber strobe light
Plugs and Sockets

¹ Includes all-motion alarm and amber strobe light.

4069LE

A. Platform height – elevated	12.19 m
B. Platform height – lowered	1.73 m
C. Platform railing height ¹	1.10 m
D. Stowed height (rails folded)	2.04 m
E. Platform size	1.65 m x 2.92 m
F. Deck extension	0.91 m
G. Overall width ²	1.75 m
H. Overall length ²	3.07 m
I. Wheelbase	2.32 m
J. Ground clearance	0.20 m
Platform capacity	360 kg
Capacity on deck extension	120 kg
Lift/lower time	54/50 sec.
Maximum drive height	9.14 m
Machine weight ¹ ²	5,300 kg
Maximum ground bearing pressure	9.4 kg/cm ²
Drive speed – lowered	4.8 km/h
Drive speed – elevated	0.8 km/h
Gradeability	35%
Turning radius – inside	2.29 m
Turning radius – outside	4.88 m
Tyres (non-marking)	240/55-17.5
Brakes	Automatic Spring Applied
Drive motors	Dual Electric Traction
Hydraulic Pump Motor	Perm Magnet
Batteries	8 x 6V 370 A/hr
Charger (120/240V - 50/60HZ)	23 Amp SCR Automatic
Hydraulic pump	Gear Pump
Hydraulic system	32 L
Generator set	—
Generator fuel tank	—

¹ Certain weight and dimensions may vary due to options and to compliance with country standards.

² Dimensions with optional levelling jacks are; Length 3.73 m, Width 1.75 m, Weight +400kg.

Certain options or country standards may increase weight and/or dimensions.

