

Platform

0.76 m x 1.52 m low mount platform
Side entry with inward swing gate
Multiple function operation
Full proportional drive joystick control with integral thumb steer switch
Full proportional main boom and swing joystick control
Variable speed dial control for lower boom, telescope, platform rotate and jib (E/M450AJ)
Selectable creep speed on drive / lift and swing functions
1.24 m articulating jib
180 degree powered platform rotator
Platform console machine status light panel¹
Load sensing system
AC power cable to platform

Functional Equipment & Accessories

3 degree tilt alarm and indicator light
240/55 - 17.5 foam filled tyres
Lifting/tie down lugs
Ground control selector switch with key lock
Battery condition indicator
Hour meter
Horn
Platform tool tray
Manual descent system

Available Options

0.76 m x 1.22 m low mount platform
13 mm air line to platform
Non mark solid rubber tyres
240/55 - 17.5 non marking foam filled tyres
All motion alarm
Alarm package²
Platform worklights
Head and tail lights
Light package³
Amber strobe light
Plugs & Sockets
Acrylic console shield
Cylinder bellows
Corner storage tray

Power & Transmission

Two Wheel Direct Electric Drive
8 x 6V 370 A/hr deep cycle batteries
Automatic traction control
Programmable "Personality" settings
On-board self-diagnostic testing
Enclosed battery / electrical compartment
23 amp automatic battery charger
Automatic rear wheel brakes
Sculptured ABS hoods

¹ Provides indicator lights at platform control console for system distress, low battery, tilt light, and foot switch status.

² Includes all-motion alarm and amber strobe light.



E450AJ

Platform height	13.72 m
Horizontal outreach	7.24 m
Up and over height	7.70 m
Swing (non-continuous)	360°
Platform capacity – unrestricted	230 kg
Platform rotator (hydraulic)	180°
Jib – overall length	1.24 m
Jib - range of articulation	141° (+86° / -55°)
A. Platform size	0.76 m x 1.52 m
B. Overall width	1.75 m
C. Tailswing (working condition)	Zero
D. Stowed height	2.01 m
E. Stowed length	6.45 m
F. Wheelbase	2.01 m
G. Ground clearance	0.20 m
Machine weight ¹	6,670 kg
Drive speed	5.2 km/h
Gradeability	30%
Tyres	240/55-17.5 Foam Filled
Turning radius – inside	0.61 m
Turning radius – outside	3.15 m
Electrical system	48V DC
Batteries	8 x 6V 370 A/hr
Drive motors	Dual Electric Traction
Brakes	Automatic Spring Applied
Hydraulic motor	Perm. Magnet
Hydraulic pump	Gear Pump
Hydraulic reservoir	20 L

¹Certain options or country specifications may increase weight and/or dimensions.
Specifications may change to meet country standards or with the addition of optional equipment.

